

## Flat suction cup (round)

SUF 60 NBR-55 M10x1.25-IG N009

Part no...:10.01.01.13953

<https://www.schmalz.com/10.01.01.13953>

Home > Vacuum Technology for Automation > Vacuum Components > Vacuum Suction Cups > Flat Suction Cups (Round) > Flat Suction Cups SUF > SUF 60 NBR-55 M10x1.25-IG N009

### Flat suction cup (round) f. process- safe handling of smooth or slightly rough surfaces



Size: 60

Suction cup material: Nitrile rubber NBR

Material hardness [Shore A]: 55 Shore A

### Design Data



Attribute	Value
Dmax(S)	66.40 mm
Ds	60 mm
G1	M10x1.25-F
H	17 mm
LG1	6 mm
Z (Stroke)	5.50 mm

### Technical Data

Attribute	Value
Suction force (-600mbar)	140 N
Pull-off force	140 N
Volume	12.70 cm <sup>3</sup>
Curve radius (min) (convex)	75 mm
Hose diameter (empf.) d	6 mm
Size	60
Suction cup material	Nitrile rubber NBR
Material hardness [Shore A]	55 Shore A

### Contact Schmalz

Schmalz Sp.z.o.o. | ul. Fabianowska 131/A1, 62-052 Komorniki, Poland | +48 61 628 67 70 | [schmalz@schmalz.pl](mailto:schmalz@schmalz.pl)

## Flat suction cup (round)

SUF 60 NBR-55 M10x1.25-IG N009

Part no...:10.01.01.13953

<https://www.schmalz.com/10.01.01.13953>

Weight	31 g
Product family	SUF

Note: Suction force: The specified suction forces are theoretical values at a vacuum of -0.6 bar and with a dry, smooth and flat workpiece surface - they do not include a safety factor Hose diameter: The recommended hose diameter refers to a hose length of approx. 2 m

### Accessories



#### TVN G1/4-AG 9 N009

Part no...:10.05.10.00065

Thread G1: G1/4"-M

Thread G2: M10x1.25-M

Spring stroke Z: 9 mm

Nipple: N 009