

Flat suction cup (round)

SUF 100 HT1-60 M10x1.25-IG N009

Part no.:10.01.01.14001

<https://www.schmalz.com/10.01.01.14001>

Home > Vacuum Technology for Automation > Vacuum Components > Vacuum Suction Cups > Flat Suction Cups (Round) > Flat Suction Cups SUF > SUF 100 HT1-60 M10x1.25-IG N009

Flat suction cup (round) f. process- safe handling of smooth or slightly rough surfaces



Size: 100

Suction cup material: High temp material HT1

Material hardness [Shore A]: 60 Shore A

Design Data



Attribute	Value
Dmax(S)	108 mm
Ds	100 mm
G1	M10x1.25-F
H	19 mm
LG1	6 mm
Z (Stroke)	7.50 mm

Technical Data

Attribute	Value
Suction force (-600mbar)	402 N
Pull-off force	402 N
Volume	46.40 cm ³
Curve radius (min) (convex)	200 mm
Hose diameter (empf.) d	6 mm
Size	100
Suction cup material	High temp material HT1
Material hardness [Shore A]	60 Shore A

Contact Schmalz

Schmalz Sp.z.o.o. | ul. Fabianowska 131/A1, 62-052 Komorniki, Poland | +48 61 628 67 70 | schmalz@schmalz.pl

Flat suction cup (round)

SUF 100 HT1-60 M10x1.25-IG N009

Part no.:10.01.01.14001

<https://www.schmalz.com/10.01.01.14001>

Weight	104.50 g
Product family	SUF

Note: Suction force: The specified suction forces are theoretical values at a vacuum of -0.6 bar and with a dry, smooth and flat workpiece surface - they do not include a safety factor Hose diameter: The recommended hose diameter refers to a hose length of approx. 2 m

Accessories



TVN G1/4-AG 9 N009

Part no.:10.05.10.00065

Thread G1: G1/4"-M

Thread G2: M10x1.25-M

Spring stroke Z: 9 mm

Nipple: N 009