

Eaton 10NHFF000BI-400

Catalog Number: 10NHFF000BI-400

Fuse-link, LV, 10 A, AC 400 V, NH000, gFF, IEC, dual indicator, insulated gripping lugs

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	10NHFF000BI-400
	Packing Unit
	Case Pack
	Pack
EAN	Quantity
5027590369596	60
5027590369268	3
Gross Weight	Length
8.3 kg	420 mm
0.34 kg	83 mm
Width	Height
180 mm	180 mm
78 mm	56 mm
Volume	ERP Name
13608 cm ³	SAP-UNITY
362.544 cm ³	SAP-UNITY
Product Length/Depth	Product Height
79 mm	51 mm
Product Width	Product Weight
21 mm	113.3333333 g
Compliances	Certifications
CE Marked	IEC 60269-1
RoHS Compliant	IEC 60269-2
	DIN 43620



Type

Fuse

Application

industrial

Amperage Rating

10 A

Fitted with:

Insulated metal gripping lugs

Fuse size

NH000

Current type

AC

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated switching capacity

120 kA

Rated voltage AC

400 V

Class

Class gFF

Fuse type

Square body with knife blade contact

Utilization category

gFF(full-range, extra fast operation)

Color

None

Interrupt rating

120 kAIC

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

Yes

Watt losses

1.7 W

Connection

Blade end

Construction

NH000

Construction size

NH000

Fuse shape

Square body

Knife blade contacts

Voltage type

AC

Suitable for

Microswitch 170H0236

EBF Vertical fuse rail

EBV Vertical fuse switch-disconnectors

EBH Size 000 Horizontal fuse switch-disconnectors

Material

Ceramic body

Quantity

3

Voltage rating

400 V

Fuse system (according to IEC 60269)

Fuse system A

Rated switching capacity AC

120 kA



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. Wszelkie
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)