

Eaton 160NHFF00BI-400

Catalog Number: 160NHFF00BI-400

Fuse-link, LV, 160 A, AC 400 V, NH00, gFF, IEC, dual indicator, insulated gripping lugs



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	160NHFF00BI-400
	Packing Unit
	Pack
	Case Pack
EAN	Quantity
5027590369299	3
5027590369626	72
Gross Weight	Length
0.497 kg	102 mm
15.048 kg	350 mm
Width	Height
80 mm	63 mm
220 mm	220 mm
Volume	ERP Name
514.08 cm ³	SAP-UNITY
16940 cm ³	SAP-UNITY
Product Length/Depth	Product Height
79 mm	57 mm
Product Width	Product Weight
30 mm	166 g
Compliances	Certifications
CE Marked	IEC 60269-1
RoHS Compliant	IEC 60269-2
	DIN 43620

Type

Fuse

Application

industrial

Amperage Rating

160 A

Fitted with:

Insulated metal gripping lugs

Fuse size

NH00

Current type

AC

Breaking capacity

80 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated switching capacity

80 kA

Rated voltage AC

400 V

Class

Class gFF

Fuse type

Square body with knife blade contact

Utilization category

gFF(full-range, extra fast operation)

Color

None

Interrupt rating

80 kAIC

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

Yes

Watt losses

13 W

Connection

Blade end

Construction

NH00

Construction size

NH00

Fuse shape

Knife blade contacts

Square body

Voltage type

AC

Suitable for

SD00-D Single pole NH Fuse base

TD00-D Tripe pole NH Fuse base

Microswitch 170H0236

Material

Ceramic body

Quantity

3

Voltage rating

400 V

Fuse system (according to IEC 60269)

Fuse system A

Rated switching capacity AC

80 kA



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. Wszelkie
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)