

# Eaton 160NHG1BI-690

Catalog Number: 160NHG1BI-690

Fuse-link, LV, 160 A, AC 690 V, NH1, gL/gG, IEC, dual indicator, insulated gripping lugs



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series low voltage NH Fuse	160NHG1BI-690
	<b>Packing Unit</b>
	Pack
	Case Pack
<b>EAN</b>	<b>Quantity</b>
5027590248389	3
5027590272087	36
<b>Gross Weight</b>	<b>Length</b>
1.222 kg	137 mm
15.5 kg	430 mm
<b>Width</b>	<b>Height</b>
134 mm	68 mm
290 mm	160 mm
<b>Volume</b>	<b>ERP Name</b>
1248.344 cm <sup>3</sup>	SAP-UNITY
19952 cm <sup>3</sup>	SAP-UNITY
<b>Product Length/Depth</b>	<b>Product Height</b>
135 mm	63 mm
<b>Product Width</b>	<b>Product Weight</b>
40 mm	407.3333333 g
<b>Compliances</b>	<b>Certifications</b>
CE Marked	IEC 60269-1
RoHS Compliant	IEC 60269-2
	DIN 43620

## Electrical data

### Amperage Rating

160 A

### Voltage rating

690 V

### Voltage type

AC

### Breaking capacity

120 kA

### Frequency rating - min

45 Hz

### Frequency rating - max

62 Hz

## Product specification

### Fuse size

NH1

### Insulated metal gripping lugs (IMGL)

Yes

## Accessories

### Suitable for

SD1-D Single pole NH Fuse base

TD1-D Tripe pole NH Fuse base

Microswitch 170H0236

EBH Size 00 to 4 Horizontal fuse switch-disconnectors

## Do pobrania

### Biuletyny usług serwisowych

Datasheet - 160NHG1BI-690 (PL)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. Wszelkie  
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



Eaton.com/socialmedia