

Eaton 160NHG2BWP

Catalog Number: 160NHG2BWP

Fuse-link, LV, 160 A, AC 500 V, NH2, gL/gL, IEC, dual indicator, live gripping lugs, weather resistant



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	160NHG2BWP
	Packing Unit
	Pack
	Case Pack
EAN	Quantity
5027590532938	3
5027590532952	24
Gross Weight	Length
1.954 kg	153 mm
16.474 kg	385 mm
Width	Height
172 mm	76 mm
280 mm	175 mm
Volume	ERP Name
2000.016 cm ³	SAP-UNITY
19272 cm ³	SAP-UNITY
Product Length/Depth	Product Height
150 mm	71 mm
Product Width	Product Weight
53 mm	651.333 g
Compliances	Certifications
CE	IEC 60269-1
CE Marked	IEC 60269-2
RoHS Compliant	DIN 43620

Electrical data

Amperage Rating

160 A

Voltage rating

500 V

Voltage type

AC

Breaking capacity

120 kA

Frequency rating - min

45 Hz

Frequency rating - max

62 Hz

Product specification

Fuse size

NH2

Insulated metal gripping lugs (IMGL)

No

Accessories

Suitable for

SD2-D Single pole NH Fuse base

TD2-D Tripe pole NH Fuse base

Microswitch 170H0235

Microswitch 170H0236

Do pobrania



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. Wszelkie
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)