

Eaton 200NHFF1BI-400

Catalog Number: 200NHFF1BI-400

Fuse-link, LV, 200 A, AC 400 V, NH1, gFF, IEC, dual indicator, insulated gripping lugs

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	200NHFF1BI-400
	Packing Unit
	Case Pack
	Pack
EAN	Quantity
5027590369671	36
5027590369343	3
Gross Weight	Length
15.5 kg	0 mm
1.044 kg	137 mm
Width	Height
0 mm	0 mm
134 mm	68 mm
Volume	ERP Name
0 cm ³	SAP-UNITY
1248.344 cm ³	SAP-UNITY
Product Length/Depth	Product Height
135 mm	63 mm
Product Width	Product Weight
40 mm	348 g
Compliances	Certifications
CE Marked	IEC 60269-1
RoHS Compliant	IEC 60269-2
	DIN 43620



Type

fuse

Application

industrial

Amperage Rating

200 A

Fitted with:

Insulated metal gripping lugs

Fuse size

NH1

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated voltage AC

400 V

Class

Class gFF

Fuse type

Square body with knife blade contact

Utilization category

gFF(full-range, extra fast operation)

Interrupt rating

120 kAIC

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

Yes

Connection

Blade end

Construction

NH1

Construction size

NH1

Fuse shape

Square body

Knife blade contacts

Suitable for

SD1-D Single pole NH Fuse base

TD1-D Tripe pole NH Fuse base

Microswitch 170H0236

Material

Ceramic body

Quantity

3

Voltage rating

400 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. Wszelkie
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)