

# Eaton 200NHG02BI-400

Catalog Number: 200NHG02BI-400

Fuse-link, LV, 200 A, AC 400 V, NH02, gL/gG, IEC, dual indicator, insulated gripping lugs



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series low voltage NH Fuse	200NHG02BI-400
<b>Product Name</b>	<b>Packing Unit</b>
Eaton Bussmann series low voltage NH Fuse	Case Pack
<b>Product Name</b>	<b>Packing Unit</b>
Eaton Bussmann series low voltage NH Fuse	Pack
<b>EAN</b>	<b>Quantity</b>
5027590342193	36
5027590145657	3
<b>Gross Weight</b>	<b>Length</b>
16.125 kg	420 mm
1.348 kg	152 mm
<b>Width</b>	<b>Height</b>
320 mm	175 mm
132 mm	76 mm
<b>Volume</b>	<b>ERP Name</b>
23520 cm <sup>3</sup>	SAP-UNITY
1524.864 cm <sup>3</sup>	SAP-UNITY
<b>Product Length/Depth</b>	<b>Product Height</b>
150 mm	63 mm
<b>Product Width</b>	<b>Product Weight</b>
40 mm	449.3333333 g
<b>Compliances</b>	<b>Certifications</b>
RoHS Compliant	IEC 60269-1
CE Marked	IEC 60269-2
	DIN 43620

## Type

Fuse

Biuletyny usług serwisowych

Datasheet - 200NHG02BI-400 (PL)

## Application

industrial  
Utilities, Solar, Wind

## Amperage Rating

200 A

## Fitted with:

Insulated metal gripping lugs

## Fuse size

NH02

## Current type

AC

## Breaking capacity

120 kA

## Frequency rating - max

62 Hz

## Frequency rating - min

45 Hz

## Rated switching capacity

120 kA

## Rated voltage AC

400 V

## Class

Class gG/gL

## Fuse type

Square body with knife blade contact

## Utilization category

gL/gG (cable protection/equipment protection)

## Interrupt rating

120 kAIC

## Fuse indicator

Combination fuse status indicator

## Insulated metal gripping lugs (IMGL)

Yes

Watt losses

12 W

Connection

Blade end

Construction

NH02

Construction size

NH02

Fuse shape

Knife blade contacts

Square body

Voltage type

AC

Suitable for

Microswitch BVL50

Material

Ceramic body

Quantity

3

Voltage rating

400 V

Rated switching capacity AC

120 kA