

Eaton 200NHG2BWP

Catalog Number: 200NHG2BWP

Fuse-link, LV, 200 A, AC 500 V, NH2, gL/gL, IEC, dual indicator, live gripping lugs, weather resistant



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	200NHG2BWP
	Packing Unit
	Case Pack
	Pack
EAN	Quantity
5027590529334	24
5027590529327	3
Gross Weight	Length
16.474 kg	385 mm
1.954 kg	153 mm
Width	Height
280 mm	175 mm
172 mm	76 mm
Volume	ERP Name
19272 cm ³	SAP-UNITY
2000.016 cm ³	SAP-UNITY
Product Length/Depth	Product Height
150 mm	71 mm
Product Width	Product Weight
53 mm	651.333 g
Compliances	Certifications
CE	IEC 60269-1
CE Marked	IEC 60269-2
RoHS Compliant	DIN 43620

Electrical data

Amperage Rating

200 A

Voltage rating

500 V

Voltage type

AC

Breaking capacity

120 kA

Frequency rating - min

45 Hz

Frequency rating - max

62 Hz

Product specification

Fuse size

NH2

Insulated metal gripping lugs (IMGL)

No

Accessories

Suitable for

SD2-D Single pole NH Fuse base

TD2-D Tripe pole NH Fuse base

Microswitch 170H0235

Microswitch 170H0236

Do pobrania



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. Wszelkie
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)