

Eaton 224NHG02BI

Catalog Number: 224NHG02BI

Fuse-link, LV, 224 A, AC 500 V, NH02, gL/gG, IEC, dual indicator, insulated gripping lugs



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	224NHG02BI
	Packing Unit
	Case Pack
	Pack
EAN	Quantity
5027590342414	36
5027590146081	3
Gross Weight	Length
15.199 kg	385 mm
1.326 kg	152 mm
Width	Height
280 mm	175 mm
132 mm	76 mm
Volume	ERP Name
19193.65 cm ³	SAP-UNITY
1524.864 cm ³	SAP-UNITY
Product Length/Depth	Product Height
150 mm	63 mm
Product Width	Product Weight
39 mm	442 g
Compliances	Certifications
CE	IEC 60269-1
RoHS Compliant	IEC 60269-2
CE Marked	DIN 43620

Type

Fuse

Application

industrial

Amperage Rating

224 A

Fitted with:

Metal gripping lugs

Fuse size

NH3

Current type

AC

Breaking capacity

120 kA

Rated switching capacity

120 kA

Rated voltage AC

500 V

Class

Class gG/gL

Fuse type

Square body with knife blade contact

Accessory/spare part type

SDL-3 Solid link

FEH- Fuse extraction handle

SD3-SK Shroud kit

SD3-PB 2-phase barriers and 2 ganging links

TD3-IP20 Triple pole protection kit

Utilization category

gL/gG (cable protection/equipment protection)

Interrupt rating

120 kAIC

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

Yes

Biuletyny usług serwisowych

Datasheet - 224NHG02BI (PL)

Watt losses

18 W

Connection

Blade end

Construction

NH02

Construction size

NH02

Fuse shape

Square body

Knife blade contacts

Voltage type

AC

Suitable for

SD3-D Single pole NH Fuse base

TD3-D Tripe pole NH Fuse base

Microswitch 170H0235

EBH Size 00 to 4 Horizontal fuse switch-disconnectors

Material

Ceramic body

Quantity

3

Voltage rating

500 V

Rated switching capacity AC

120 kA