

# Eaton 250NHG02B-400

Catalog Number: 250NHG02B-400

Fuse-link, LV, 250 A, AC 400 V, NH02, gL/gG, IEC, dual indicator, live gripping lugs



## General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	250NHG02B-400
	Packing Unit
	Case Pack
	Pack
EAN	Quantity
5027590342520	36
5027590131704	3
Gross Weight	Length
16.125 kg	420 mm
1.28 kg	152 mm
Width	Height
320 mm	175 mm
132 mm	76 mm
Volume	ERP Name
23520 cm <sup>3</sup>	SAP-UNITY
1524.864 cm <sup>3</sup>	SAP-UNITY
Product Length/Depth	Product Height
150 mm	63 mm
Product Width	Product Weight
40 mm	427 g
Compliances	Certifications
RoHS Compliant	IEC 60269-1
CE Marked	IEC 60269-2
	DIN 43620

## Type

Fuse

Biuletyny usług serwisowych

[Datasheet - 250NHG02B-400 \(PL\)](#)

## Application

industrial  
Utilities, Solar, Wind

## Amperage Rating

250 A

## Fitted with:

Metal gripping lugs

## Fuse size

NH02

## Current type

AC

## Breaking capacity

120 kA

## Frequency rating - max

62 Hz

## Frequency rating - min

45 Hz

## Rated switching capacity

120 kA

## Rated voltage AC

400 V

## Class

Class gG/gL

## Fuse type

Square body with knife blade contact

## Utilization category

gL/gG (cable protection/equipment protection)

## Interrupt rating

120 kAIC

## Fuse indicator

Combination fuse status indicator

## Insulated metal gripping lugs (IMGL)

No

Watt losses

14 W

Connection

Blade end

Construction

NH02

Construction size

NH02

Fuse shape

Square body

Knife blade contacts

Voltage type

AC

Suitable for

Microswitch BVL50

Material

Ceramic body

Quantity

3

Voltage rating

400 V

Rated switching capacity AC

120 kA