

Eaton 250NHG02BI-400

Catalog Number: 250NHG02BI-400

Fuse-link, LV, 250 A, AC 400 V, NH02, gL/gG, IEC, dual indicator, insulated gripping lugs



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	250NHG02BI-400
EAN	Packing Unit
5027590342551	Case Pack
5027590132541	Pack
Gross Weight	Quantity
15.199 kg	36
1.222 kg	3
Width	Length
280 mm	385 mm
132 mm	152 mm
Volume	Height
19193.65 cm ³	175 mm
1524.864 cm ³	76 mm
Product Length/Depth	ERP Name
150 mm	SAP-UNITY
Product Width	SAP-UNITY
40 mm	Product Height
Compliances	63 mm
RoHS Compliant	Product Weight
CE Marked	407.3333333 g
	Certifications
	IEC 60269-1
	IEC 60269-2
	DIN 43620

Type

Fuse

Biuletyny usług serwisowych

Datasheet - 250NHG02BI-400 (PL)

Application

industrial
Utilities, Solar, Wind

Amperage Rating

250 A

Fitted with:

Insulated metal gripping lugs

Fuse size

NH02

Current type

AC

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated switching capacity

120 kA

Rated voltage AC

400 V

Class

Class gG/gL

Fuse type

Square body with knife blade contact

Utilization category

gL/gG (cable protection/equipment protection)

Interrupt rating

120 kAIC

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

Yes

Watt losses

14 W

Connection

Blade end

Construction

NH02

Construction size

NH02

Fuse shape

Knife blade contacts

Square body

Voltage type

AC

Suitable for

Microswitch BVL50

Material

Ceramic body

Quantity

3

Voltage rating

400 V

Rated switching capacity AC

120 kA