

Eaton 250NHG02BI

Catalog Number: 250NHG02BI

Eaton Bussmann series low voltage NH Fuse, 500V, 250A, 120 kAIC, Combination fuse status indicator, Class C gL/gG



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	250NHG02BI
	Packing Unit
	Pack
	Case Pack
	Quantity
EAN	
5027590132466	3
5027590342544	36
Gross Weight	Length
1.222 kg	152 mm
15.199 kg	385 mm
Width	Height
132 mm	76 mm
280 mm	175 mm
Volume	ERP Name
1524.864 cm ³	SAP-UNITY
19193.65 cm ³	SAP-UNITY
Product Length/Depth	Product Height
150 mm	63 mm
Product Width	Product Weight
39 mm	407.3333333 g
Compliances	Certifications
RoHS Compliant	IEC 60269-1
CE Marked	IEC 60269-2
	DIN 43620

Type

fuse

Application

industrial
Utilities, Solar, Wind

Amperage Rating

250 A

Fitted with:

Insulated metal gripping lugs

Fuse size

NH02

Current type

AC

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated switching capacity

120 kA

Rated voltage AC

500 V

Class

Class gG/gL

Fuse type

Square body with knife blade contact

Utilization category

gL/gG (cable protection/equipment protection)

Interrupt rating

120 kAIC

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

Yes

Connection

Blade end

Construction

NH02

Construction size

NH02

Fuse shape

Square body

Knife blade contacts

Voltage type

AC

Suitable for

Microswitch BVL50

Material

Ceramic body

Quantity

3

Voltage rating

500 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. Wszelkie
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia