

Eaton 250NHG2B-690

Catalog Number: 250NHG2B-690

Eaton Bussmann series low voltage NH Fuse, Live gripping lug, 690V, 250A, 120 kAIC, Combination fuse status indicator, fuse, Blade end connection, Class C gL/gG, Square-body with knife blade contact, Ceramic body



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	250NHG2B-690
	Packing Unit
	Case Pack
	Pack
EAN	Quantity
5027590364249	24
5027590248471	3
Gross Weight	Length
16.474 kg	365 mm
1.952 kg	153 mm
Width	Height
320 mm	165 mm
172 mm	76 mm
Volume	ERP Name
19272 cm ³	SAP-UNITY
2000.016 cm ³	SAP-UNITY
Product Length/Depth	Product Height
150 mm	71 mm
Product Width	Product Weight
54 mm	651 g

Compliances

RoHS Compliant

Certifications

IEC 60269-1

Electrical data

Amperage Rating

250 A

Voltage rating

690 V

Voltage type

AC

Breaking capacity

120 kA

Frequency rating - min

45 Hz

Frequency rating - max

62 Hz

Product specification

DIN 43620

Model Code

NH FUSE 250A 690V gG SIZE 2

Fuse size

NH2

Insulated metal gripping lugs (IMGL)

No

Accessories

Suitable for

SD2-D Single pole NH Fuse base

TD2-D Tripe pole NH Fuse base

Microswitch 170H0235

Microswitch 170H0236

EBH Size 00 to 4 Horizontal fuse switch-disconnectors

Do pobrania



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. Wszelkie
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia