

Eaton 250NHG2BI-690

Catalog Number: 250NHG2BI-690

Fuse-link, LV, 250 A, AC 690 V, NH2, gL/gL, IEC, dual indicator, insulated gripping lugs



General specifications

| | |
|---|-----------------------|
| Product Name | Catalog Number |
| Eaton Bussmann series low voltage NH Fuse | 250NHG2BI-690 |
| Product Name | Packing Unit |
| Eaton Bussmann series low voltage NH Fuse | Case Pack |
| Product Name | Packing Unit |
| Eaton Bussmann series low voltage NH Fuse | Pack |
| EAN | Quantity |
| 5027590272148 | 24 |
| 5027590248563 | 3 |
| Gross Weight | Length |
| 16.04 kg | 360 mm |
| 1.952 kg | 153 mm |
| Width | Height |
| 320 mm | 170 mm |
| 172 mm | 76 mm |
| Volume | ERP Name |
| 19584 cm ³ | SAP-UNITY |
| 2000.016 cm ³ | SAP-UNITY |
| Product Length/Depth | Product Height |
| 150 mm | 71 mm |
| Product Width | Product Weight |
| 54 mm | 651 g |
| Compliances | Certifications |
| CE Marked | IEC 60269-1 |
| RoHS Compliant | IEC 60269-2 |
| | DIN 43620 |

Electrical data

Amperage Rating

250 A

Voltage rating

690 V

Voltage type

AC

Breaking capacity

120 kA

Frequency rating - min

45 Hz

Frequency rating - max

62 Hz

Product specification

Fuse size

NH1

Insulated metal gripping lugs (IMGL)

Yes

Accessories

Suitable for

SD1-D Single pole NH Fuse base

TD1-D Tripe pole NH Fuse base

Microswitch 170H0236

EBH Size 00 to 4 Horizontal fuse switch-disconnectors

Do pobrania

Biuletyny usług serwisowych

Datasheet - 250NHG2BI-690 (PL)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. Wszelkie
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia