

Eaton 25NHG01B

Catalog Number: 25NHG01B

Eaton Bussmann series low voltage NH Fuse, Live gripping lug, 500V, 25A, 120 kAIC, Combination fuse status indicator, fuse, Blade end connection, Class C gL/gG, Square-body with knife blade contact, Ceramic body



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	25NHG01B
	Packing Unit
	Case Pack
	Pack
EAN	Quantity
5027590363730	36
5027590147767	3
Gross Weight	Length
11.208 kg	325 mm
0.884 kg	137 mm
Width	Height
290 mm	155 mm
102 mm	68 mm
Volume	ERP Name
14608.75 cm ³	SAP-UNITY
950.232 cm ³	SAP-UNITY
Product Length/Depth	Product Height
135 mm	57.8 mm
Product Width	Product Weight
29.55 mm	295 g

Compliances

Certifications

CE Marked

IEC 60269-1

defaultTaxonomyAttributeLabel

Do pobrania

DIN 43620

Type

fuse

Special features

Live gripping lug

Application

industrial

Utilities, Solar, Wind

Amperage Rating

25 A

Fitted with:

Metal gripping lugs

Fuse size

NH0

Current type

AC

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated switching capacity

120 kA

Rated voltage AC

500 V

Class

Class gG/gL

Fuse type

Square body with knife blade contact

Utilization category

gL/gG (cable protection/equipment protection)

Interrupt rating

120 kAIC

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Connection

Blade end

Construction

NH01

Construction size

NH01

Fuse shape

Square body

Knife blade contacts

Voltage type

AC

Suitable for

EBF Vertical fuse rail

EBV Vertical fuse switch-disconnectors

Material

Ceramic body

Quantity

3

Voltage rating

500 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. Wszelkie
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia