
Item no.: 281-659
Product description: 4-conductor disconnect terminal block with disconnect tab



Produkt kann von Bild abweichen / product may differ

Packing unit 50 pieces

RoHS compliant

Product group	1 (Rail Mounted Terminal Blocks)
Cross section [mm ²]	0.08 - 4 mm ²
Cross section [AWG]	28 - 12 AWG
Connection method	CAGE CLAMP®CONNECTION
Measured voltage EN	400 V
Measured shock voltage	6 kV
Pollution degree	3
Current intensity EN	10 A
Weight	13.554 g
Color	grey
Wiring type	Front-entry
No. of connection Points	4
No. of potentials	2
Height	53.5 mm
Height	2.11 in
Width	6 mm
Width	0.236 in
Depth	86 mm
Depth	3.39 in

Strip length from	9 mm
Strip length to	10 mm
Strip length	0.37 in
Mounting	TS 35



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
281-659	ABS	05-HG476175/3-PDA	400	10	4,0
281-659	BV	07436/Co	400	10	4,0
281-659	CCA	NL5591/1	400	10	4
281-659	CSA	154112-1505034	600	15	28-12
281-659	DNV	E-10423	800	32	4,0
281-659	KEMA	2076376.01	400	10	4
281-659	KR	HMB05880-EL001	500/800	10/35	4
281-659	LR	91/20112(E6)	400	10	4,0
281-659	PRS	TE/1718/880590/08	400	10	4
281-659	UR	E45172	300	15	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected