

# Eaton 300NHG2B

Catalog Number: 300NHG2B

Fuse-link, LV, 300 A, AC 500 V, NH2, gL/gG, IEC, dual indicator, live gripping lugs

## General specifications



Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	300NHG2B
	Packing Unit
	Case Pack
	Pack
EAN	Quantity
5027590364287	24
5027590225328	3
Gross Weight	Length
16.474 kg	365 mm
1.952 kg	153 mm
Width	Height
320 mm	165 mm
172 mm	76 mm
Volume	ERP Name
19272 cm <sup>3</sup>	SAP-UNITY
2000.016 cm <sup>3</sup>	SAP-UNITY
Product Length/Depth	Product Height
150 mm	71 mm
Product Width	Product Weight
54 mm	651 g
Compliances	Certifications
CE Marked	IEC 60269-1
RoHS Compliant	IEC 60269-2
	DIN 43620

**Type**

Fuse

Biuletyny usług serwisowych

Datasheet - 300NHG2B (PL)

**Application**

Industrial, Utilities, Solar, Wind

**Amperage Rating**

300 A

**Fitted with:**

Metal gripping lugs

**Fuse size**

NH2

**Current type**

AC

**Breaking capacity**

120 kA

**Rated switching capacity**

120 kA

**Rated voltage AC**

500 V

**Class**

Class gG/gL

**Fuse type**

Square body with knife blade contact

**Accessory/spare part type**

SDL-2 Solid link

FEH- Fuse extraction handle

SD12-SK Shroud kit

SD12-PB 2-phase barriers and 2 ganging links

TD2-IP20 Triple pole protection kit

**Utilization category**

gL/gG (cable protection/equipment protection)

**Interrupt rating**

120 kAIC

**Fuse indicator**

Combination fuse status indicator

**Insulated metal gripping lugs (IMGL)**

No

#### Watt losses

20 W

#### Connection

Blade end

#### Construction

NH2

#### Construction size

NH2

#### Fuse shape

Knife blade contacts

Square body

#### Voltage type

AC

#### Suitable for

SD2-D Single pole NH Fuse base

TD2-D Tripe pole NH Fuse base

Microswitch 170H0235

Microswitch 170H0236

EBH Size 00 to 4 Horizontal fuse switch-disconnectors

#### Material

Ceramic body

#### Quantity

3

#### Voltage rating

500 V

#### Rated switching capacity AC

120 kA