

Eaton 315NHFF2BI-400

Catalog Number: 315NHFF2BI-400

Fuse-link, LV, 315 A, AC 400 V, NH2, gFF, IEC, dual indicator, insulated gripping lugs



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	315NHFF2BI-400
	Packing Unit
	Case Pack
	Pack
EAN	Quantity
5027590369725	24
5027590369398	3
Gross Weight	Length
16.04 kg	360 mm
1.545 kg	153 mm
Width	Height
320 mm	170 mm
172 mm	76 mm
Volume	ERP Name
19584 cm ³	SAP-UNITY
2000.016 cm ³	SAP-UNITY
Product Length/Depth	Product Height
150 mm	71 mm
Product Width	Product Weight
54 mm	515 g
Compliances	Certifications
CE Marked	IEC 60269-1
RoHS Compliant	IEC 60269-2
	DIN 43620

Electrical data

Amperage Rating

315 A

Voltage rating

400 V

Voltage type

AC

Breaking capacity

120 kA

Frequency rating - min

45 Hz

Frequency rating - max

62 Hz

Product specification

Fuse size

NH2

Insulated metal gripping lugs (IMGL)

Yes

Accessories

Suitable for

SD2-D Single pole NH Fuse base

TD2-D Tripe pole NH Fuse base

Microswitch 170H0235

Microswitch 170H0236

Do pobrania



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. Wszelkie
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)