

Eaton 315NHG03B

Catalog Number: 315NHG03B

Eaton Bussmann series low voltage NH Fuse, Live gripping lug, 500V, 315A, 120 kAIC, Combination fuse status indicator, fuse, Blade end connection, Class C gL/gG, Square-body with knife blade contact, Ceramic body

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	315NHG03B
	Packing Unit
	Pack
	Case Pack
EAN	Quantity
5027590199315	3
5027590364294	24
Gross Weight	Length
1.958 kg	152 mm
16.41 kg	365 mm
Width	Height
174 mm	88 mm
320 mm	195 mm
Volume	ERP Name
2327.424 cm ³	SAP-UNITY
22776 cm ³	SAP-UNITY
Product Length/Depth	Product Height
150 mm	71 mm
Product Width	Product Weight
54 mm	612.667 g



Compliances

Certifications

CE Marked

IEC 60269-1

defaultTaxonomyAttributeLabel

Do pobrania

DIN 43620

Type

fuse

Special features

Live gripping lug

Application

industrial

Utilities, Solar, Wind

Amperage Rating

315 A

Fitted with:

Metal gripping lugs

Fuse size

NH02

Current type

AC

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated switching capacity

120 kA

Rated voltage AC

500 V

Class

Class gG/gL

Fuse type

Square body with knife blade contact

Utilization category

gL/gG (cable protection/equipment protection)

Interrupt rating

120 kAIC

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Connection

Blade end

Construction

NH03

Construction size

NH03

Fuse shape

Square body

Knife blade contacts

Voltage type

AC

Suitable for

Microswitch BVL50

Material

Ceramic body

Quantity

3

Voltage rating

500 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. Wszelkie
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)