

# Eaton 315NHG2BI-690

Catalog Number: 315NHG2BI-690

Fuse-link, LV, 315 A, AC 690 V, NH2, gL/gL, IEC, dual indicator, insulated gripping lugs



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series low voltage NH Fuse	315NHG2BI-690
<b>EAN</b>	<b>Packing Unit</b>
5027590272155	Case Pack
5027590248570	Pack
<b>Gross Weight</b>	<b>Quantity</b>
16.04 kg	24
1.952 kg	3
<b>Width</b>	<b>Length</b>
320 mm	360 mm
172 mm	153 mm
<b>Volume</b>	<b>Height</b>
19584 cm <sup>3</sup>	170 mm
2000.016 cm <sup>3</sup>	76 mm
<b>Product Length/Depth</b>	<b>ERP Name</b>
150 mm	SAP-UNITY
<b>Product Width</b>	SAP-UNITY
54 mm	<b>Product Height</b>
<b>Compliances</b>	71 mm
RoHS Compliant	<b>Product Weight</b>
CE Marked	651 g
	<b>Certifications</b>
	IEC 60269-1
	IEC 60269-2
	DIN 43620

## Electrical data

### Amperage Rating

315 A

### Voltage rating

690 V

### Voltage type

AC

### Breaking capacity

120 kA

### Frequency rating - min

45 Hz

### Frequency rating - max

62 Hz

## Product specification

### Fuse size

NH4

### Insulated metal gripping lugs (IMGL)

Yes

## Accessories

### Suitable for

SD4-S NH Fuse base

EBH Size 00 to 4 Horizontal fuse switch-disconnectors

## Do pobrania

### Biuletyny usług serwisowych

Datasheet - 315NHG2BI-690 (PL)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. Wszelkie  
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



Eaton.com/socialmedia