

Eaton 32NHG0B

Catalog Number: 32NHG0B

Eaton Bussmann series low voltage NH Fuse, 500V, 32A, 120 kAIC, Combination fuse status indicator, fuse, Class C gL/gG

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	32NHG0B
	Packing Unit
	Pack
	Case Pack
EAN	Quantity
5027590199797	3
5027590363785	36
Gross Weight	Length
0.898 kg	127 mm
10.354 kg	270 mm
Width	Height
102 mm	63 mm
220 mm	220 mm
Volume	ERP Name
816.102 cm ³	SAP-UNITY
13068 cm ³	SAP-UNITY
Product Length/Depth	Product Height
125 mm	58 mm
Product Width	Product Weight
30 mm	299.3333333 g
Compliances	Certifications
RoHS Compliant	IEC 60269-1
CE Marked	IEC 60269-2
	DIN 43620



Type

fuse

Application

industrial

Utilities, Solar, Wind

Amperage Rating

32 A

Fitted with:

Metal gripping lugs

Fuse size

NH0

Current type

AC

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated switching capacity

120 kA

Rated voltage AC

500 V

Class

Class gG/gL

Fuse type

Square body with knife blade contact

Utilization category

gL/gG (cable protection/equipment protection)

Interrupt rating

120 kAIC

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Connection

Blade end

Construction

NH0

Construction size

NH0

Fuse shape

Square body

Knife blade contacts

Voltage type

AC

Suitable for

EBF Vertical fuse rail

EBV Vertical fuse switch-disconnectors

Material

Ceramic body

Quantity

3

Voltage rating

500 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. Wszelkie
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)