

Eaton 355NHG03BI

Catalog Number: 355NHG03BI

Fuse-link, LV, 355 A, AC 500 V, NH03, gL/gG, IEC, dual indicator, insulated gripping lugs



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	355NHG03BI
	Packing Unit
	Case Pack
	Pack
EAN	Quantity
5027590364539	24
5027590146135	3
Gross Weight	Length
16.41 kg	385 mm
1.97 kg	152 mm
Width	Height
280 mm	175 mm
174 mm	88 mm
Volume	ERP Name
22776 cm ³	SAP-UNITY
2327.424 cm ³	SAP-UNITY
Product Length/Depth	Product Height
150 mm	75 mm
Product Width	Product Weight
53 mm	657 g
Compliances	Certifications
RoHS Compliant	IEC 60269-1
CE Marked	IEC 60269-2
	DIN 43620

Type

Fuse

Biuletyny usług serwisowych

Datasheet - 355NHG03BI (PL)

Application

industrial
Utilities, Solar, Wind

Amperage Rating

355 A

Fitted with:

Insulated metal gripping lugs

Fuse size

NH03

Current type

AC

Breaking capacity

120 kA

Rated switching capacity

120 kA

Rated voltage AC

500 V

Class

Class gG/gL

Fuse type

Square body with knife blade contact

Utilization category

gL/gG (cable protection/equipment protection)

Interrupt rating

120 kAIC

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

Yes

Watt losses

27 W

Connection

Blade end

Construction

NH03

Construction size

NH03

Fuse shape

Square body

Knife blade contacts

Voltage type

AC

Suitable for

Microswitch BVL50

Material

Ceramic body

Quantity

3

Voltage rating

500 V

Rated switching capacity AC

120 kA



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. Wszelkie
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia