

Eaton 355NHG2BI

Catalog Number: 355NHG2BI

Fuse-link, LV, 355 A, AC 500 V, NH2, gL/gL, IEC, dual indicator, insulated gripping lugs



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	355NHG2BI
	Packing Unit
	Case Pack
	Pack
EAN	Quantity
5027590364607	24
5027590146104	3
Gross Weight	Length
16.474 kg	385 mm
1.978 kg	153 mm
Width	Height
280 mm	175 mm
172 mm	76 mm
Volume	ERP Name
19272 cm ³	SAP-UNITY
2000.016 cm ³	SAP-UNITY
Product Length/Depth	Product Height
150 mm	75 mm
Product Width	Product Weight
53 mm	659 g
Compliances	Certifications
CE Marked	IEC 60269-1
RoHS Compliant	IEC 60269-2
	DIN 43620

Electrical data

Amperage Rating

355 A

Voltage rating

500 V

Voltage type

AC

Breaking capacity

120 kA

Product specification

Fuse size

NH2

Insulated metal gripping lugs (IMGL)

Yes

Accessories

Suitable for

SD2-D Single pole NH Fuse base

TD2-D Tripe pole NH Fuse base

Microswitch 170H0235

Microswitch 170H0236

EBH Size 00 to 4 Horizontal fuse switch-disconnectors

Do pobrania

Biuletyny usług serwisowych

Datasheet - 355NHG2BI (PL)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. Wszelkie
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)