

# Eaton 35NHG0B

Catalog Number: 35NHG0B

Eaton Bussmann series low voltage NH Fuse, 500V, 35A, 120 kAIC, Combination fuse status indicator, fuse, Class C gL/gG



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series low voltage NH Fuse	35NHG0B
	<b>Packing Unit</b>
	Pack
	Case Pack
<b>EAN</b>	<b>Quantity</b>
5027590200080	3
5027590363822	36
<b>Gross Weight</b>	<b>Length</b>
0.898 kg	127 mm
10.354 kg	270 mm
<b>Width</b>	<b>Height</b>
102 mm	63 mm
220 mm	220 mm
<b>Volume</b>	<b>ERP Name</b>
816.102 cm <sup>3</sup>	SAP-UNITY
13068 cm <sup>3</sup>	SAP-UNITY
<b>Product Length/Depth</b>	<b>Product Height</b>
125 mm	58 mm
<b>Product Width</b>	<b>Product Weight</b>
30 mm	299.3333333 g
<b>Compliances</b>	<b>Certifications</b>
RoHS Compliant	IEC 60269-1
CE Marked	IEC 60269-2
	DIN 43620

**Type**

fuse

**Application**

industrial  
Utilities, Solar, Wind

**Amperage Rating**

35 A

**Fitted with:**

Metal gripping lugs

**Fuse size**

NH01

**Current type**

AC

**Breaking capacity**

120 kA

**Frequency rating - max**

62 Hz

**Frequency rating - min**

45 Hz

**Rated switching capacity**

120 kA

**Rated voltage AC**

500 V

**Class**

Class gG/gL

**Fuse type**

Square body with knife blade contact

**Utilization category**

gL/gG (cable protection/equipment protection)

**Interrupt rating**

120 kAIC

**Fuse indicator**

Combination fuse status indicator

**Insulated metal gripping lugs (IMGL)**

No

Connection

Blade end

Construction

NH0

Construction size

NH0

Fuse shape

Knife blade contacts

Square body

Voltage type

AC

Suitable for

Microswitch 170H0235

Material

Ceramic body

Quantity

3

Voltage rating

500 V



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. Wszelkie  
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)