

# Eaton 400NHFF2BI-400

Catalog Number: 400NHFF2BI-400

Fuse-link, LV, 400 A, AC 400 V, NH2, gFF, IEC, dual indicator, insulated gripping lugs



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series low voltage NH Fuse	400NHFF2BI-400
	<b>Packing Unit</b>
	Pack
	Case Pack
<b>EAN</b>	<b>Quantity</b>
5027590369435	3
5027590369763	24
<b>Gross Weight</b>	<b>Length</b>
1.545 kg	153 mm
16.04 kg	360 mm
<b>Width</b>	<b>Height</b>
172 mm	76 mm
320 mm	170 mm
<b>Volume</b>	<b>ERP Name</b>
2000.016 cm <sup>3</sup>	SAP-UNITY
19584 cm <sup>3</sup>	SAP-UNITY
<b>Product Length/Depth</b>	<b>Product Height</b>
150 mm	71 mm
<b>Product Width</b>	<b>Product Weight</b>
54 mm	515 g
<b>Compliances</b>	<b>Certifications</b>
CE Marked	IEC 60269-1
RoHS Compliant	IEC 60269-2
	DIN 43620

## Electrical data

### Amperage Rating

400 A

### Voltage rating

400 V

### Voltage type

AC

### Breaking capacity

120 kA

### Frequency rating - min

45 Hz

### Frequency rating - max

62 Hz

## Product specification

### Fuse size

NH2

### Insulated metal gripping lugs (IMGL)

Yes

## Accessories

### Suitable for

SD2-D Single pole NH Fuse base

TD2-D Tripe pole NH Fuse base

Microswitch 170H0235

Microswitch 170H0236

## Do pobrania



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. Wszelkie  
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)