

Eaton 400NHM3B

Catalog Number: 400NHM3B

Fuse-link, low voltage, 400 A, AC 500 V, NH3, aM, IEC, dual indicator



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	400NHM3B
	Packing Unit
	Case Pack
	Pack
	Quantity
EAN	
5027590364843	12
5027590328661	3
Gross Weight	Length
14 kg	330 mm
3.418 kg	240 mm
Width	Height
265 mm	210 mm
152 mm	95 mm
Volume	ERP Name
18364.5 cm ³	SAP-UNITY
3465.6 cm ³	SAP-UNITY
Product Length/Depth	Product Height
150 mm	71 mm
Product Width	Product Weight
76 mm	1140 g
Compliances	Certifications
CE Marked	IEC 60269-1
RoHS Compliant	IEC 60269-2
	DIN 43620

Type

Fuse

Application

industrial

Amperage Rating

400 A

Fitted with:

Metal gripping lugs

Fuse size

NH3

Current type

AC

Breaking capacity

120 kA

Rated switching capacity

120 kA

Rated voltage AC

500 V

Class

Class aM

Fuse type

Square body with knife blade contact

Accessory/spare part type

SDL-3 Solid link

FEH- Fuse extraction handle

SD3-SK Shroud kit

SD3-PB 2-phase barriers and 2 ganging links

TD3-IP20 Triple pole protection kit

Utilization category

aM (switchgear protection)

Interrupt rating

120 kAIC

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Watt losses

28 W

Connection

Blade end

Construction

NH3

Construction size

NH3

Fuse shape

Square body

Knife blade contacts

Voltage type

AC

Suitable for

SD3-D Single pole NH Fuse base

TD3-D Tripe pole NH Fuse base

Microswitch 170H0235

EBH Size 00 to 4 Horizontal fuse switch-disconnectors

Material

Ceramic body

Quantity

3

Voltage rating

500 V

Rated switching capacity AC

120 kA