

Eaton 40NHG000BI-690

Catalog Number: 40NHG000BI-690

Eaton Fuse-link, LV, 40 A, AC 690 V, NH000, gL/gL, IEC, dual indicator, insulated gripping lugs



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	40NHG000BI-690
	Packing Unit
	Pack
	Case Pack
	Quantity
EAN	
5027590532655	3
5027590532679	60
Gross Weight	Length
0.454 kg	83 mm
8.205 kg	420 mm
Width	Height
78 mm	56 mm
180 mm	140 mm
Volume	ERP Name
362.544 cm ³	SAP-UNITY
10584 cm ³	SAP-UNITY
Product Length/Depth	Product Height
79 mm	51 mm
Product Width	Product Weight
21 mm	119.333 g
Compliances	
CE Marked	
RoHS conform	

Type

Fuse

Application

industrial

Amperage Rating

40 A

Current type

AC

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated switching capacity

120 kA

Rated voltage AC

690 V

Class

Class gG

Fuse type

Square body with knife blade contact

Utilization category

gL/gG (cable protection/equipment protection)

Color

None

Interrupt rating

120 kAIC

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

Yes

Watt losses

4 W

Connection

Blade end

Construction

NH000

Construction size

NH000

Fuse shape

Knife blade contacts

Square body

Voltage type

AC

Suitable for

Microswitch 170H0236

EBF Vertical fuse rail

EBV Vertical fuse switch-disconnectors

EBH Size 000 Horizontal fuse switch-disconnectors

Material

Ceramic body

Voltage rating

690 V

Fuse system (according to IEC 60269)

Fuse system A

Rated switching capacity AC

120 kA



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. Wszelkie
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)