

Eaton 63NHG00BI-690

Catalog Number: 63NHG00BI-690

Fuse-link, LV, 63 A, AC 690 V, NH00, gL/gG, IEC, dual indicator, insulated gripping lugs

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	63NHG00BI-690
	Packing Unit
	Pack
	Case Pack
EAN	Quantity
5027590248204	3
5027590267731	24
Gross Weight	Length
0.59 kg	102 mm
15.048 kg	350 mm
Width	Height
80 mm	63 mm
220 mm	220 mm
Volume	ERP Name
514.08 cm ³	SAP-UNITY
16940 cm ³	SAP-UNITY
Product Length/Depth	Product Height
79 mm	58 mm
Product Width	Product Weight
30 mm	197 g
Compliances	Certifications
CE Marked	IEC 60269-1
RoHS Compliant	IEC 60269-2
	DIN 43620



Type

Fuse

Biuletyny usług serwisowych

Datasheet - 63NHG00BI-690 (PL)

Application

industrial
Utilities, Solar, Wind

Amperage Rating

63 A

Fitted with:

Insulated metal gripping lugs

Fuse size

NH00

Current type

AC

Breaking capacity

120 kA

Rated switching capacity

120 kA

Rated voltage AC

690 V

Class

Class gG/gL

Fuse type

Square body with knife blade contact

Accessory/spare part type

SDL-00 Solid link
FEH- Fuse extraction handle
TD00-IP20 IP protection kit
TD00-IP20I Integral protection kit
TD00-IP20IC Integral Triple pole protection kit including fuse covers

Utilization category

gL/gG (cable protection/equipment protection)

Interrupt rating

120 kAIC

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

Yes

Connection

Blade end

Construction

NH00

Construction size

NH00

Fuse shape

Square body

Knife blade contacts

Voltage type

AC

Suitable for

SD00-D Single pole NH Fuse base

TD00-D Tripe pole NH Fuse base

Microswitch 170H0236

EBH Size 00 to 4 Horizontal fuse switch-disconnectors

Material

Ceramic body

Quantity

3

Voltage rating

690 V

Rated switching capacity AC

120 kA