

	1	2	3	4	5	6	7	8	9	10	11	12	13	14																															
A	Technische Daten Eingang: 195-264 V ~, 50/60 Hz, 1,0 A Anschluss Stromversorgung: Eurostecker (Typ C, CEE 7/16) Anschlussart: F-Buchse Eingangsbuchsen: 4x SAT, 1x TER Ausgangsbuchsen: 8x Anzahl der anschließbaren Satelliten: 1 Unterstützt DiSEqC 2.0: nein Übertragungsarten: DAB, DAB+, FM, UKW, DVB-T, DVB-T2 Unterstützt: HDTV, 3D, HD, 4K, 8K UHD, Sky Frequenzbereich: SAT: 950 ~ 2150 MHz TER: 47 ~ 862 MHz Verstärkung: SAT: -4 ~ 6 dB TER: 0 ~ 6 dB Entkopplung: SAT > TER: 28 dB TER > SAT: 30 dB Kreuz-Polarisationsentkopplung H/V: 25 dB Entkopplung: OUT-OUT SAT: 30 dB OUT-OUT TER: 22 dB Rückflusdämpfung : SAT IN: 10 dB SAT OUT: 8 dB TER IN: 8 dB TER OUT: 8 dB Ausgangspegel : SAT (IMD3 35 dB): 100 dBµV TER (IMD3 60 dB): 88 dBµV Wellenwiderstand IN/OUT: 75 Ω Stromaufnahme vom Receiver: 100 mA Stromaufnahme LNB: 800 mA Max. Leistungsaufnahme: 45 W Schaltbefehle: 13 V ---/ 22 KHz, 18 V ---/ 22 KHz, 13 V ---/ 0 KHz, 18 V ---/ 0 KHz Betriebstemperatur: 0 ~ +50 °C Lagertemperatur: -40 ~ +70 °C Gewicht: 660 g Specifications Input: 195-264 V ~, 50/60 Hz, 1.0 A Connector power supply: Euro plug (Type C, CEE 7/16) Connector type: F connector female Input connectors: 4x SAT, 1x TER Output connectors: 8x Number of satellites that can be connected: 1 Supports DiSEqC 2.0: no Transmission modes: DAB, DAB+, FM, UKW, DVB-T, DVB-T2 Supports: HDTV, 3D, HD, 4K, 8K UHD, Sky Frequency range: SAT: 950 ~ 2150 MHz TER: 47 ~ 862 MHz Gain: SAT: -4 ~ 6 dB TER: 0 ~ 6 dB Isolation: SAT > TER: 28 dB TER > SAT: 30 dB Cross-polarisation isolation H/V: 25 dB Isolation: OUT-OUT SAT: 30 dB OUT-OUT TER: 22 dB Return loss: SAT IN: 10 dB SAT OUT: 8 dB TER IN: 8 dB TER OUT: 8 dB Output level: SAT (IMD3 35 dB): 100 dBµV TER (IMD3 60 dB): 88 dBµV Impedance IN/OUT: 75 Ω Current consumption from receiver: 100 mA LNB remote current: 800 mA Max. power consumption: 45 W Switching: 13 V ---/ 22 KHz, 18 V ---/ 22 KHz, 13 V ---/ 0 KHz, 18 V ---/ 0 KHz Operating temperature: 0 ~ +50 °C Storage temperature: -40 ~ +70 °C Weight: 660 g <tr><td>I</td><td colspan="14"> Änderungen Datum Name Bezeichnung Blatt Datum Name gez.: 24.08.2023 anw gepr.: 24.08.2023 anw Norm: Änderungen vorbehalten / Subject to change 64874 SAT MULTISWITCH 05/08 GMS-0508PQ Zeichnungs-Nr.: von  2/2 <tr><td>J</td><td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><td>12</td><td>13</td><td>14</td><td>J</td></tr></td></tr>														I	Änderungen Datum Name Bezeichnung Blatt Datum Name gez.: 24.08.2023 anw gepr.: 24.08.2023 anw Norm: Änderungen vorbehalten / Subject to change 64874 SAT MULTISWITCH 05/08 GMS-0508PQ Zeichnungs-Nr.: von  2/2 <tr><td>J</td><td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><td>12</td><td>13</td><td>14</td><td>J</td></tr>														J	1	2	3	4	5	6	7	8	9	10	11	12	13	14	J
I	Änderungen Datum Name Bezeichnung Blatt Datum Name gez.: 24.08.2023 anw gepr.: 24.08.2023 anw Norm: Änderungen vorbehalten / Subject to change 64874 SAT MULTISWITCH 05/08 GMS-0508PQ Zeichnungs-Nr.: von  2/2 <tr><td>J</td><td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><td>12</td><td>13</td><td>14</td><td>J</td></tr>														J	1	2	3	4	5	6	7	8	9	10	11	12	13	14	J															
J	1	2	3	4	5	6	7	8	9	10	11	12	13	14	J																														

Specifications

Input: 195-264 V ~, 50/60 Hz, 1.0 A
Connector power supply: Euro plug (Type C, CEE 7/16)
Connector type: F connector female
Input connectors: 4x SAT, 1x TER
Output connectors: 8x
Number of satellites that can be connected: 1
Supports DiSEqC 2.0: no
Transmission modes: DAB, DAB+, FM, UKW, DVB-T, DVB-T2
Supports: HDTV, 3D, HD, 4K, 8K UHD, Sky
Frequency range: SAT: 950 ~ 2150 MHz
TER: 47 ~ 862 MHz
Gain: SAT: -4 ~ 6 dB
TER: 0 ~ 6 dB
Isolation: SAT > TER: 28 dB
TER > SAT: 30 dB
Cross-polarisation isolation H/V: 25 dB
Isolation: OUT-OUT SAT: 30 dB
OUT-OUT TER: 22 dB
Return loss: SAT IN: 10 dB
SAT OUT: 8 dB
TER IN: 8 dB
TER OUT: 8 dB
Output level: SAT (IMD3 35 dB): 100 dBµV
TER (IMD3 60 dB): 88 dBµV
Impedance IN/OUT: 75 Ω
Current consumption from receiver: 100 mA
LNB remote current: 800 mA
Max. power consumption: 45 W
Switching: 13 V ---/ 22 KHz, 18 V ---/ 22 KHz,
13 V ---/ 0 KHz, 18 V ---/ 0 KHz
Operating temperature: 0 ~ +50 °C
Storage temperature: -40 ~ +70 °C
Weight: 660 g

