



SIMATIC ET 200SP, digital output module, DQ 4x 24VDC/2A Standard, suitable for BU type A0, Color code CC02, Module diagnostics

| General information | |
|---|-------------------------------------|
| Product type designation | DQ 4x24 V DC/2 A ST |
| HW functional status | From FS08 |
| Firmware version | V1.1 |
| • FW update possible | Yes |
| usable BaseUnits | BU type A0 |
| Color code for module-specific color identification plate | CC02 |
| Product function | |
| • I&M data | Yes; I&M0 to I&M3 |
| • Isochronous mode | No |
| Engineering with | |
| • STEP 7 TIA Portal configurable/integrated from version | V11 SP2 / V13 |
| • STEP 7 configurable/integrated from version | V5.5 SP3 / - |
| • PCS 7 configurable/integrated from version | V8.1 SP1 |
| • PROFIBUS from GSD version/GSD revision | GSD Revision 5 |
| • PROFINET from GSD version/GSD revision | GSDML V2.3 |
| Operating mode | |
| • DQ | Yes |
| • DQ with energy-saving function | No |
| • PWM | No |
| • Oversampling | No |
| • MSO | No |
| Supply voltage | |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 19.2 V |
| permissible range, upper limit (DC) | 28.8 V |
| Reverse polarity protection | Yes |
| Input current | |
| Current consumption, max. | 60 mA; without load |
| output voltage / header | |
| Rated value (DC) | 24 V |
| Power loss | |
| Power loss, typ. | 1 W |
| Address area | |
| Address space per module | |
| • Address space per module, max. | 1 byte; + 1 byte for QI information |
| Hardware configuration | |
| Automatic encoding | |
| • Mechanical coding element | Yes |
| • Type of mechanical coding element | Type A |

| | |
|--|--|
| Selection of BaseUnit for connection variants | |
| <ul style="list-style-type: none"> • 1-wire connection • 2-wire connection • 3-wire connection • 4-wire connection | BU type A0 BU type A0 BU type A0 with AUX terminals or potential distributor module BU type A0 + Potential distributor module |
| Digital outputs | |
| Type of digital output | Source output (PNP, current-sourcing) |
| Number of digital outputs | 4 |
| Current-sinking | No |
| Current-sourcing | Yes |
| Digital outputs, parameterizable | Yes |
| Short-circuit protection | Yes |
| <ul style="list-style-type: none"> • Response threshold, typ. | 2.8 to 5.2 A |
| Limitation of inductive shutdown voltage to | Typ. L+ (-50 V) |
| Controlling a digital input | Yes |
| Switching capacity of the outputs | |
| <ul style="list-style-type: none"> • with resistive load, max. • on lamp load, max. | 2 A 10 W |
| Load resistance range | |
| <ul style="list-style-type: none"> • lower limit • upper limit | 12 Ω 3 400 Ω |
| Output current | |
| <ul style="list-style-type: none"> • for signal "1" rated value • for signal "0" residual current, max. | 2 A 0.1 mA |
| Output delay with resistive load | |
| <ul style="list-style-type: none"> • "0" to "1", typ. • "0" to "1", max. • "1" to "0", typ. • "1" to "0", max. | 50 μs 50 μs 100 μs 100 μs |
| Parallel switching of two outputs | |
| <ul style="list-style-type: none"> • for uprating • for redundant control of a load | No Yes |
| Switching frequency | |
| <ul style="list-style-type: none"> • with resistive load, max. • with inductive load, max. • on lamp load, max. | 100 Hz 2 Hz 10 Hz |
| Total current of the outputs | |
| <ul style="list-style-type: none"> • Current per channel, max. • Current per module, max. | 2 A 8 A |
| Total current of the outputs (per module) | |
| horizontal installation | |
| — up to 40 °C, max. | 8 A |
| — up to 50 °C, max. | 6 A |
| — up to 60 °C, max. | 4 A |
| vertical installation | |
| — up to 30 °C, max. | 8 A |
| — up to 40 °C, max. | 6 A |
| — up to 50 °C, max. | 4 A |
| — up to 60 °C, max. | 4 A |
| Cable length | |
| <ul style="list-style-type: none"> • shielded, max. • unshielded, max. | 1 000 m 600 m |
| Interrupts/diagnostics/status information | |
| Diagnostics function | Yes |
| Substitute values connectable | Yes |
| Alarms | |
| <ul style="list-style-type: none"> • Diagnostic alarm | Yes |
| Diagnoses | |
| <ul style="list-style-type: none"> • Monitoring the supply voltage • Wire-break • Short-circuit | Yes Yes; Module-wise Yes; Module-wise |

| | |
|--|--|
| • Group error | Yes |
| Diagnostics indication LED | |
| • Monitoring of the supply voltage (PWR-LED) | Yes; green PWR LED |
| • Channel status display | Yes; green LED |
| • for channel diagnostics | No |
| • for module diagnostics | Yes; green/red DIAG LED |
| Potential separation | |
| Potential separation channels | |
| • between the channels | No |
| • between the channels and backplane bus | Yes |
| • between the channels and the power supply of the electronics | No |
| Isolation | |
| Isolation tested with | 707 V DC (type test) |
| Standards, approvals, certificates | |
| Suitable for safety functions | No |
| Suitable for safety-related tripping of standard modules | Yes; see FAQ Entry ID: 39198632 |
| Highest safety class achievable in safety mode | |
| • Performance level according to ISO 13849-1 | PL d |
| • SIL acc. to IEC 61508 | SIL 2 |
| Ambient conditions | |
| Ambient temperature during operation | |
| • horizontal installation, min. | -30 °C; < 0 °C as of FS08 |
| • horizontal installation, max. | 60 °C |
| • vertical installation, min. | -30 °C; < 0 °C as of FS08 |
| • vertical installation, max. | 50 °C |
| Altitude during operation relating to sea level | |
| • Installation altitude above sea level, max. | 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual |
| Dimensions | |
| Width | 15 mm |
| Height | 73 mm |
| Depth | 58 mm |
| Weights | |
| Weight, approx. | 30 g |

last modified: 8/16/2023 