

Eaton 6NHG000BI-400

Catalog Number: 6NHG000BI-400

Fuse-link, LV, 6 A, AC 400 V, NH000, gL/gG, IEC, dual indicator, insulated gripping lugs



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	6NHG000BI-400
	Packing Unit
	Case Pack
	Pack
	Quantity
EAN	60
5027590343961	3
5027590156691	
Gross Weight	Length
8.205 kg	420 mm
0.392 kg	83 mm
Width	Height
180 mm	140 mm
78 mm	56 mm
Volume	ERP Name
10584 cm ³	SAP-UNITY
362.544 cm ³	SAP-UNITY
Product Length/Depth	Product Height
79 mm	51 mm
Product Width	Product Weight
21 mm	131 g
Compliances	Certifications
RoHS Compliant	IEC 60269-1
CE Marked	IEC 60269-2
	DIN 43620

Type

Fuse

Biuletyny usług serwisowych

Datasheet - 6NHG000BI-400 (PL)

Application

industrial
Utilities, Solar, Wind

Amperage Rating

6 A

Fitted with:

Insulated metal gripping lugs

Fuse size

NH000

Current type

AC

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated switching capacity

120 kA

Rated voltage AC

400 V

Class

Class gG/gL

Fuse type

Square body with knife blade contact

Utilization category

gL/gG (cable protection/equipment protection)

Interrupt rating

120 kAIC

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

Yes

Watt losses

2.2 W

Connection

Blade end

Construction

NH000

Construction size

NH000

Fuse shape

Knife blade contacts

Square body

Voltage type

AC

Suitable for

Microswitch 170H0236

EBF Vertical fuse rail

EBV Vertical fuse switch-disconnectors

EBH Size 000 Horizontal fuse switch-disconnectors

Material

Ceramic body

Quantity

3

Voltage rating

400 V

Rated switching capacity AC

120 kA