

CARDMASTER PC 25/22-C3



Order symbol: PC 25/22-C3
Product nbr: 7520141
Description: Enclosure, PC
Remarks: Without main cover

EAN: 6418074059352
EI. number:
Finland: 3422959
Electric No. Sweden: 7520141

Including: Base, terminal compartment cover with EPDM gasket and screws for mounting plate/DIN-rail. -3 and -L3 versions: Transparent cover with PUR gasket, hinges, locking devices; FC version: Closed PC frame front plate with PUR gasket and cover screws.

Sample photo

| Dimensions: | Length | Width | Height | Accessories: |
|-------------------------------------|----------------------|-------|--------|--|
| mm: | 257 | 219 | 122 | FP 25/22 Front plate (aluminium) |
| inch: | 10.1 | 8.6 | 4.8 | FC PC 25/22 Frame of PC front plate |
| Materials: | | | | Rating: |
| Material: | Polycarbonate | | | Impact Resistance (EN 62262): IK07 |
| Base colour: | RAL 7035 -light grey | | | Electrical insulation: Totally insulated |
| Gasket material: | EPDM | | | Halogen free (DIN/VDE 0472, Part 815): 1 |
| Temperatures: | | | | UV resistance: UL 508 |
| Temperature °C (short term): | -40 ... 120 °C | | | Flammability Rating: UL 746C 5" |
| Temperature °C (continuous): | -40 ... 80 °C | | | Glow Wire Test (IEC 695-2-1) °C: 960 |
| Temperature °F (short term): | -40 ... 250 °F | | | NEMA Class: NEMA 1, 3, 3R, 12, 13 |
| Temperature °F (continuous): | -40 ... 175 °F | | | Certificates: |
| Accessories: | | | | SGS Fimko |
| MP 25/22 | Mounting plate | | | Gost R |

