

---

PRODUCT-DETAILS

## CPS25G-25

### BRAIDED SLEEVE GRY PLYE 25 DIA 25M



---

#### General Information

Extended Product Type	CPS25G-25
Product ID	7TCG054800R0045
EAN	5414363103370
Catalog Description	BRAIDED SLEEVE GRY PLYE 25 DIA 25M
Long Description	Non-Flame Retardant Braided Sleeve, Gray Polyester for Temperatures up to 150 Celsius (302 F), Nominal Diameter 25mm (0.984 Inches), Expandable Diameter Range 18mm (0.709 Inches) to 34mm (1.34 Inches), Mini-Reel Length 25m (82.02 Feet)

---

#### Ordering

EAN	5414363103370
UPC	786210623368
Country of Origin	France (FR)
Customs Tariff Number	3926909990
Selling Unit of Measure	roll

---

#### Dimensions

Product Net Depth / Length	82.02 ft 25 m
----------------------------	------------------

---

#### Container Information

---

Package Level 1 Units	1 reel
Package Level 2 Units	5 reel
Package Level 2 Width	6.3 in 160 mm
Package Level 2 Height	3.9 in 99 mm
Package Level 2 Depth / Length	6.8 in 173 mm

---

### Additional Information

Brand / Label	Catamount
Bundle Diameter	0.04 to 2.6 in 1 to 66 mm
Color	Gray
Effective Date	19980621
Material	Polyester
Product Name	Plastic conduit
Product Type	Braided Sleeve
Temperature Range	-58 to 302 °F -50 to 150 °C

---

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	CPS25G-25
Instructions and Manuals	CPS25G-25

---

### Classifications

ETIM 6	EC001937 - Cable protection for installation duct
ETIM 7	EC001937 - Cable protection for installation duct
ETIM 8	EC001937 - Cable protection for installation duct
UNSPSC	39131602
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5392 >> Expandable braided sleeving

---

### Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

