

PRODUCT-DETAILS

CPS40G-50-CV0

GREY BRD SLEEVING CONF. V0, 50M



General Information

Extended Product Type	CPS40G-50-CV0
Product ID	7TCG054800R0080
EAN	5414363406938
Catalog Description	GREY BRD SLEEVING CONF. V0, 50M
Long Description	Flame Retardant Braided Sleeve, Gray Polyester for Temperatures -50 Degrees Celsius (-58 F) up to 150 Celsius (302 F), Nominal Diameter 40mm (1.57 Inches), Expandable Diameter Range 30mm (1.18 Inches) to 50mm (1.97 Inches), Mini-Reel Length 50m (164.04 Feet)

Ordering

EAN	5414363406938
UPC	786209889386
Country of Origin	France (FR)
Customs Tariff Number	5607502500
Selling Unit of Measure	roll

Dimensions

Product Net Depth / Length	164.04 ft 50 m
----------------------------	-------------------

Container Information

Package Level 1 Units	1 reel
Package Level 1 Width	8.66 in 220 mm
Package Level 1 Height	7.08 in 180 mm
Package Level 1 Depth / Length	8.66 in 220 mm
Package Level 2 Units	5 reel
Package Level 2 Width	14.76 in 375 mm
Package Level 2 Height	13.58 in 345 mm
Package Level 2 Depth / Length	29.53 in 750 mm

Additional Information

Brand / Label	Catamount
Bundle Diameter	0.04 to 2.6 in 1 to 66 mm
Color	Gray
Effective Date	20071010
Material	Polyester
Product Name	OTHER BRAIDED SLEEVING
Product Type	Braided Sleeve
Temperature Range	-58 to 302 °F -50 to 150 °C

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	CPS40G-50-CV0
Instructions and Manuals	CPS40G-50-CV0

Classifications

ETIM 6	EC001937 - Cable protection for installation duct
ETIM 7	EC001937 - Cable protection for installation duct
ETIM 8	EC001937 - Cable protection for installation duct
UNSPSC	39131602
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5392 >> Expandable braided sleeving

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

