

## ESD INTERCHANGEABLE SCREWDRIVER-SET

for special service

Practical tool rolls made from conductive material are equipped with double-ended screwdriver-blades and ESD handle with brass clamping sleeve, suitable for hexagon blades of A / F 4 mm

**Blade:** chrome vanadium, hexagon material, A / F 4 x 120 mm, hardened over its full length, matt chrome-plated, black tip

### 4-920 **BERNSTEIN** 9-piece interchangeable screwdriver set with ESD-handle

Contents: ESD-interchangeable handle  
 3 blades widths 1.5 / 3.0 mm, 2.0 / 3.5 mm, 2.5 / 4.0 mm  
 2 cross-recess blades PH 000 / PH 00, PH 0 / PH 1  
 3 TORX blades T 5 / T 6, T 7 L / T 8 L, T 9 L / T 10 L (\*L\* with bore hole)

Weight: 170 g

### 4-960 **BERNSTEIN** 11-piece interchangeable screwdriver set with ESD-handle

Contents: ESD-interchangeable handle  
 2 blades widths 1.5 / 3.0 mm, 2.0 / 4.0 mm,  
 2 cross-recess blades PH 000 / PH 00, PH 0 / PH 1  
 4 TORX blades T 3 / T 4, T 5 / T 6, T 7 L / T 8 L, T 9 L / T 10 L (\*L\* with bore hole)  
 2 Tri Wing / Four Wing blades TW 1 / FW 1, TW 2 / FW 2

Weight: 170 g



4-960

## ESD SCREWDRIVERS

with special-square pattern handle from impact-resistant, **conductive** black plastic

**Blade:** chrome vanadium, hardened over its full length, matt chrome-plated, with black tip

**Handle:** impact-resistant, **conductive**, black plastic, electrostatic discharge according to DIN EN 100015/1

### Screwdrivers

No.	Blade length mm	Blade width mm	Blade thickness mm	Handle size mm	Weight
4-632	100	4.0	0.8	92 x 21	40 g
4-633	125	5.5	1.0	100 x 23	65 g
4-643	300	5.5	1.2	100 x 23	100 g

### Cross-recess screwdrivers

No.	Size	Blade length mm	Blade Ø mm	Handle size mm	Weight
4-652	1	80	4.5	92 x 21	40 g
4-653	2	100	6.0	100 x 23	75 g

### extra long screwdrivers

4-656	1	300	4.5	100 x 23	80 g
4-657	2	300	6.0	100 x 23	115 g

### Cross-recess screwdrivers Pozidriv

4-662	1	80	4.5	92 x 21	40 g
4-663	2	100	6.0	100 x 23	70 g

### Tri Wing screwdrivers

6-641	TW 0	70	4.5	92 x 21	42 g
6-642	TW 1	70	4.5	92 x 21	42 g
6-643	TW 2	70	4.5	92 x 21	42 g
6-644	TW 3	70	4.5	92 x 21	42 g
6-645	TW 4	70	6.0	92 x 21	53 g
6-646	TW 5	70	6.0	92 x 21	54 g

