

**ARCA 806030**

**Order symbol:** ARCA 806030  
**Product nbr:** 8120019  
**Description:** Cabinet, PC  
**Remarks:** 2-point locking

**EAN:** 6418074079305  
**El. number:**  
 Finland: 3423115  
 Electric No. 8212091171  
 Denmark:  
 Electric No. Sweden: 2500122



Sample photo

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. F versions with flange opening (including gasket and screws). Door guide included.

Dimensions:				Accessories:	
	Length	Width	Height		
<b>mm:</b>	800	600	300	MPX ARCA 8060	Mounting plate (730x530 mm)
<b>inch:</b>	31.5	23.6	11.8	MPMP ARCA 8060	Mounting plate multiperforated (730x530x2 mm - □3.6 mm)
Materials:				MPP ARCA 8060	Mounting plate perforated (730x530x2 mm - 26x11 mm)
<b>Material:</b>	Polycarbonate			DRS ARCA 806025	DIN rail frame set
<b>Base colour:</b>	RAL 7035 -light grey			DRS ARCA 806030	DIN rail frame set
<b>Cover colour:</b>	RAL 7035 -light grey			IDS ARCA 8060	Inner door set
<b>Gasket material:</b>	Polyurethane			PMK ARCA 60	Pole mounting kit
Temperatures:				RCS ARCA 8060	Rain canopy set
<b>Temperature °C (short term):</b>	-40 ... 120 °C			SBK ARCA 60	Support bar kit
<b>Temperature °C (continuous):</b>	-40 ... 80 °C			SBK ARCA 80	Support bar kit
<b>Temperature °F (short term):</b>	-40 ... 250 °F			DSP ARCA LM	Door stopper ARCA, left, midsize, for 5070-8060
<b>Temperature °F (continuous):</b>	-40 ... 175 °F			DSP ARCA RM	Door stopper ARCA, right, midsize for 5070-8060

Accessories:		Rating:
MPS ARCA 8060	Mounting plate (730x530x2 mm)	Ingress Protection (EN 60529): IP66
		Impact Resistance (EN 62262): IK10 +35°C /IK08 -25°C
		Electrical insulation: Totally insulated
		Halogen free (DIN/VDE 0472, Part 815): 1
		UV resistance: UL 508
		Flammability Rating: UL 94 5VA
		Glow Wire Test (IEC 695-2-1) °C: 960

