

**ARCA 604021W**



Sample photo

**Order symbol:** ARCA 604021W  
**Product nbr:** 8120132  
**Description:** Cabinet, PC  
**Remarks:** Cover with window, 2-point locking

**EAN:** 6418074080035  
**EI. number:**  
 Finland: 3423205  
 Electric No. 8212091883  
 Denmark:  
 Electric No. Sweden: 2500152

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. F versions with flange opening (including gasket and screws). Door guide included.

Dimensions:	Length	Width	Height	Accessories:
mm:	600	400	210	MPP ARCA 6040
inch:	23.6	15.7	8.3	MPMP ARCA 6040

**Materials:**

<b>Material:</b>	Polycarbonate
<b>Base colour:</b>	RAL 7035 -light grey
<b>Cover colour:</b>	RAL 7035 -light grey
<b>Gasket material:</b>	Polyurethane

**Temperatures:**

<b>Temperature °C (short term):</b>	-40 ... 120 °C
<b>Temperature °C (continuous):</b>	-40 ... 80 °C
<b>Temperature °F (short term):</b>	-40 ... 250 °F
<b>Temperature °F (continuous):</b>	-40 ... 175 °F

**Accessories:**

MPS ARCA 6040	Mounting plate (550x350x2 mm)
---------------	-------------------------------

MPX ARCA 6040	Mounting plate multiperforated (550x350x2 mm - □3.6 mm)
DRS ARCA 604021	Mounting plate (550x350 mm)
DRS ARCA 604030	DIN rail frame set
IDS ARCA 6040	DIN rail frame set
PMK ARCA 40	Inner door set
RCS ARCA 6040	Pole mounting kit
SBK ARCA 40	Rain canopy set
SBK ARCA 60	Support bar kit
DSP ARCA VLS	Support bar kit
DSP ARCA VRS	Door stopper ARCA, vertical, left, small
	Door stopper ARCA, vertical, right, small

**Rating:**

Ingress Protection (EN 60529): IP65  
 Impact Resistance (EN 62262): IK08  
 Electrical insulation: Totally insulated  
 Halogen free (DIN/VDE 0472, Part 815): 1  
 UV resistance: UL 508  
 Flammability Rating: UL 94 5VA  
 Glow Wire Test (IEC 695-2-1) °C: 960

**Certificates:**

SGS Fimko  
 Gost R

