

**ARCA 806030W**



Sample photo

**Order symbol:** ARCA 806030W  
**Product nbr:** 8120139  
**Description:** Cabinet, PC  
**Remarks:** Cover with window, 2-point locking

**EAN:** 6418074080103  
**EI. number:**  
 Finland: 3423215  
 Electric No. 8212091951  
 Denmark:  
 Electric No. Sweden: 2500156

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. F versions with flange opening (including gasket and screws). Door guide included.

Dimensions:	Length	Width	Height	Accessories:
mm:	800	600	300	MPX ARCA 8060 MPMP ARCA 8060
inch:	31.5	23.6	11.8	
<b>Materials:</b>				MPP ARCA 8060
<b>Material:</b>	Polycarbonate			DRS ARCA 806025
<b>Base colour:</b>	RAL 7035 -light grey			DRS ARCA 806030
<b>Cover colour:</b>	RAL 7035 -light grey			IDS ARCA 8060
<b>Gasket material:</b>	Polyurethane			PMK ARCA 60
<b>Temperatures:</b>				RCS ARCA 8060
<b>Temperature °C (short term):</b>	-40 ... 120 °C			SBK ARCA 60
<b>Temperature °C (continuous):</b>	-40 ... 80 °C			SBK ARCA 80
<b>Temperature °F (short term):</b>	-40 ... 250 °F			DSP ARCA LM
<b>Temperature °F (continuous):</b>	-40 ... 175 °F			DSP ARCA RM

Accessories:	Rating:
MPS ARCA 8060	Ingress Protection (EN 60529): IP65
Mounting plate (730x530x2 mm)	Impact Resistance (EN 62262): IK08
	Electrical insulation: Totally insulated
	Halogen free (DIN/VDE 0472, Part 815): 1
	UV resistance: UL 508
	Flammability Rating: UL 94 5VA
	Glow Wire Test (IEC 695-2-1) °C: 960

