



# Product: <u>83320E</u> ☑

Electronic, 2 C #20 Str SPC, TFE Ins, OA SPC Brd, TFE Jkt, MIL-W-16878/4 (Type E)

😭 Request Sample

# **Product Description**

High Temperature Electronic, 2 Conductor 20AWG (19x32) Silver Plated Copper, TFE Insulation, Overall Silver Plated Copper Braid(85%) Shield, TFE Outer Jacket, MIL-W-16878/4 (Type E)

# **Technical Specifications**

# **Product Overview**

Suitable Applications: MIL-W-16878/4 (Type E) Spec;				vpe E) Spec;	Extreme High/Low Temper	ature Environme	ts; up to 600V analog signals & voltage contr
onstructi	on Details						
onductor							
Element	No. of Elements	Size	Stranding	Mat	erial		
Conductor(s)	2	20 AWG	19x32	SC - Silver	red Copper		
nsulation							
Element	Materia	al	Nom.	Thickness	Nom. Insulation Diamete	r Color Code	

#### Outer Jacket

Outer Sacket			
Material	Nom. Thickness	Nom. Diameter	
PTFE - Polytetrafluoroethylene	0.011 in (0.28 mm)	0.159 in (4.04 mm)	
Overall Cable Diameter (Nomin	al): 0.159 in (4.04 n	ım)	

#### **Electrical Characteristics**

#### Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
Conductor(s)	8.9 Ohm/1000ft	31.7 pF/ft (104 pF/m)	51 pF/ft (170 pF/m)	6.5 Amps per conductor @ 25°C

#### Voltage

Voltage Rating 600 V

# **Mechanical Characteristics**

1.59 in (40.4 mm) 1.59 in (40.4 mm)

# UL Temperature Operating 200°C -65°C to +200°C Bend Radius Stationary Min. Installation Min.

Max. Pull Tension:	30 lbs (14 kg)
Bulk Cable Weight:	21 lbs/1000ft

#### **Standards and Compliance**

Sustainability:	CA Prop 65
CPR Compliance:	CPR Euroclass: Eca
NEMA Compliance:	NEMA HP3
Military Compliance:	MIL-W-16878/4 (Type E except stranding), (insulated conductors)
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)

#### **Product Notes**

A.L		
Notes:		

Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

#### **History**

Update and Revision:

Revision Number: 0.545 Revision Date: 02-15-2024

# **Part Numbers**

#### Variants

ltem #	Color	Putup Type	Length	UPC	Footnote
83320E 009100	White	Reel	100 ft	612825204022	E
83320E 009500	White	Reel	500 ft	612825204046	E
83320E 0091000	White	Reel	1,000 ft	612825204039	E

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.