

Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

8460 Multi-Conductor - High-Conductivity Copper Speaker Cable Open Twisted Const



For more Information
please call

1-800-Belden1



General Description:

18 AWG stranded (7x26) ETP high-conductivity tinned copper conductors, PVC insulation, cabled.

Physical Characteristics (Overall)

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
2	18	7x26	High Conductivity TC - Tinned Copper

Total Number of Conductors: 2

Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.508

Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
Unjacketed

Overall Cable

Overall Nominal Diameter: 4.572 mm

Mechanical Characteristics (Overall)

Operating Temperature Range: -30°C To +80°C

UL Temperature Rating: 80°C (UL AWM Style 1007)

Bulk Cable Weight: 23.811 Kg/Km

Max. Recommended Pulling Tension: 222.410 N

Min. Bend Radius/Minor Axis: 45.720 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

AWM Specification: UL Style 1007 (300 V 80°C)

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Flame Test

UL Flame Test: VW-1

Plenum/Non-Plenum

Plenum (Y/N): No

8460 Multi-Conductor - High-Conductivity Copper Speaker Cable Open Twisted Const

Electrical Characteristics (Overall)

Nom. Inductance:

Inductance (μ H/m)
0.62339

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
19.3579

Max. Operating Voltage - UL:

Voltage
300 V RMS (UL AWM Style 1007)

Max. Recommended Current:

Current
5.2 Amps per conductor @ 25°C

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8460 063U1000	1,000 FT	18.000 LB	BLACK & WHITE		TW PR BLK & NAT
8460 0631000	1,000 FT	18.000 LB	BLACK & WHITE	C	TW PR BLK & NAT
8460 0635000	5,000 FT	90.000 LB	BLACK & WHITE	C	TW PR BLK & NAT

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 09-19-2012

© 2017 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).