

**PICCOLO ABS B 65 G**



Sample photo

**Order symbol:** ABS B 65 G  
**Product nbr:** 8784303  
**Description:** Enclosure, ABS  
**Remarks:** Grey cover

**EAN:** 6418074001993  
**EI. number:**  
Finland: 3423451  
Denmark: 8212001802  
Italy: 7211010  
Sweden: 2536701  
Norway:

Including: Base with screws for mounting plate/DIN-rail, cover with PUR gasket and polyamide cover screws.

| Dimensions:                   |  | Length                     | Width | Height | Rating:                                    |
|-------------------------------|--|----------------------------|-------|--------|--|
| <b>mm:</b>                    |  | 110                        | 80    | 65     | Ingress Protection (EN 60529): IP 66/67    |
| <b>inch:</b>                  |  | 4.3                        | 3.1   | 2.6    | Impact Resistance (EN 62262): IK 07        |
| <b>Materials:</b>             |  |                            |       |        | Electrical insulation: Totally insulated   |
| <b>Material:</b>              |  | ABS                        |       |        | Halogen free (DIN/VDE 0472, Part 815): Yes |
| <b>Base colour:</b>           |  | RAL 7035                   |       |        | Flammability Rating (UL 746 C 5): UL 94 HB |
| <b>Cover colour:</b>          |  | RAL 7035                   |       |        | Glow Wire Test (IEC 695-2-1) °C: 650       |
| <b>Cover screws material:</b> |  | Polyamide                  |       |        | NEMA Class: NEMA 1, 4, 4X, 6, 6P, 12, 13   |
| <b>Cover screws colour:</b>   |  | Grey                       |       |        |  |
| <b>Gasket material:</b>       |  | Polyurethane               |       |        |  |
| <b>Temperatures:</b>          |  |                            |       |        | <b>Certificates:</b>                       |
| <b>Short term:</b>            |  | -40 ... 80 °C              |       |        |  |
| <b>Continuous:</b>            |  | -40 ... 60 °C              |       |        |  |
| <b>Short term:</b>            |  | -40 ... 175 °F             |       |        |  |
| <b>Continuous:</b>            |  | -40 ... 140 °F             |       |        |  |
| <b>Accessories:</b>           |  |                            |       |        |  |
| B-MP                          |  | Mounting plate             |       |        |  |
| B-3                           |  | DIN-35 Mounting rail       |       |        |  |
| FP 22040                      |  | Wall fastening lug (2 pcs) |       |        |  |

PICCOLO 110x80x65-85

