

DIGITUS 4K - HDMI® AOC Hybrid Fiber Optic Cable with 15m removable plug

AK-330127-150-S
EAN 4016032483755



4K HDMI AOC Connection cable HDMI to HDMI 4Kx2K@60Hz 15m Detachable

This active HDMI® AOC Hybrid Fiber Optic Cable is ideally suited for transferring uncompressed video and audio data with high bandwidth over longer distances. When the HDMI Type A plug is removed, the HDMI Type D plug is uncovered. This allows you to position the cable however you like in very tight spaces thanks to the more compact dimensions of the HDMI Type D plug. In addition, the cable's plugging options are increased thanks to the removable plug (from HDMI - D to HDMI - D; from HDMI - D to HDMI - A; from HDMI A to HDMI A; from HDMI- A to HDMI - D). The hybrid construction, which uses copper and fiber optic cable, prevents electromagnetic interference. This ensures a loss-free transfer along the entire length of the cable with UHD resolution of up to 4K/60Hz and bandwidths of up to 18 Gbps. The use of fiber optic cable keeps the diameter of this active cable very low and gives it a very tight bending radius and low weight. It is ideal for use in homes, meeting rooms, and conference rooms as well as within buildings — and these are just a few of the possible uses. The simple Plug and Play installation is user-friendly; just plug it in and immediately enjoy optimal image quality. It supports numerous standards such as HDMI 2.0b, HDCP 2.2, and HDR. Some of the many audio features supported are ARC, DTS-HD Master Audio and Dolby TrueHD. Cutting edge chip technology makes it possible to transfer the full HDMI® signal spectrum while also supporting uncompressed CED and EDID with very low latency.

Outfitted with removable HDMI Type A plugs, enables easy installation thanks to narrow cable ducts (with HDMI Type D plug)

- Supports up to 4K with 50/60Hz
- Supports up to 4K 3D
- Signal transfer rate of up to 18Gbps
- Supports up to 120Hz at Full HD
- Supports 1080p 3D HFR
- Supports YUV 4:4:4
- HDCP 2.2, HDCP 1.4

- HDMI 2.0b (backwards-compatible)
- Supports Deep Color (30-bit color depth)
- Supports HDR10 (High Dynamic Range)
- Supports audio return channel (ARC)
- Supports Consumer Electronic Control (CEC)
- Supports Lip Sync (audio/video synchronization)
- Multi Stream audio/video support
- Supports 21:9 Cinemascope
- 32 channel audio support
- Dolby TrueHD capable
- Supports 8-channel LPCM, 192 kHz, 24-bit audio capability
- Supports DTS-HD Master Audio bitstream
- Supports Super Audio CD (DSD)
- Supports Super Audio CD (DSD)
- Supports DVD audio
- Supports Blu-ray Disc and HD DVD audio and video
- Supports EDID 2.0 (device recognition)
- Latency: Zero frame delay
- Cable sheath: LSZH, halogen-free
- Operating temperature: -10 °C to +50 °C
- Operating humidity: 10 - 80% RH
- Power consumption: 250 mW max.
- Supports DVI Version 1.0
- Connection 1: HDMI Type D plug - Adapter HDMI Type A plug
- Connection 2: HDMI Type D plug - Adapter HDMI Type A plug
- Color cable: black
- Connector 1: HDMI type A, plug
- Connector 2: HDMI type A, plug
- Connector surface: gold-plated
- Ferrite filter: none
- HDMI Standard: Premium High Speed HDMI with Ethernet
- HDTV Resolution max.: 4096 x 2160 Pixel, 60Hz
- HDTV Standard: Ultra HD 4K
- Hoods: Metallic housing
- Length: 15 m
- AOC - Active Optical Cable: yes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	20	10.00	44.00	45.00	36.00	71,280.00
Packaging Unit Inside	1	0.50	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.50	20.50	21.70	6.80	3,024.98
Net single without Packaging	1	0.29	20.50	21.70	6.80	3,024.98

More images:

