




## Aluminium Thin mini-ITX cooler

21mm heatsink with embedded fan provides low noise ultra compact cooling solution for Intel LGA775, LGA115X and LGA1200 processors in thin mini-ITX and mini-ITX chassis.

Spring-loaded screws and backplate mounting.

Product Code: AK-CC7129BP01

[Where to Buy](#) 

[OVERVIEW](#)

[SPECIFICATION](#)

[REVIEWS](#)

[SUPPORT](#)

[RELATED PRODUCTS](#)



## General Information

Socket Type	Intel LGA775, LGA1150, LGA1151, LGA1155, LGA1156, LGA1200
Suggestion TDP (W)	35
Cooler Dimension	87.2 x 85.2 x 21 mm
Heatsink Material	Aluminium fins and core
Installation	Metal screws and retention plate
Weight	154g
Product Code	AK-CC7129BP01

## Fan Specification

Dimensions	Ø74.5 x 11 mm
Bearing	Two Ball Bearing
Fan Speed	600 - 3000 RPM
Max Airflow	26.53 CFM
Max Air Pressure	1.81 mm-H2O

Noise Level 15 - 30.1 dB(A)

Current Rating for Fan 0.19A

Voltage Rating for Fan DC 12V


Fan Connector 4-pin PWM

Fan Life Expectancy 80,000 hours

Warranty 2 years

---

### Contents / Package -



AKASA (@akasa\_tech)



## DISCOVER

About Akasa

Where to Buy

Press Room

## SUPPORT

Legacy Products

Contact Us



Terms and Privacy

## STAY UP TO DATE!

Subscribe now for free alerts on newly added products, exclusive deals and more.

name@example.com



 ENGLISH 

© AKASA ALL RIGHT RESERVED.