

U.I. Lapp GmbH	PRODUCT INFORMATION	
	SKINDICHT® BLK / BLK-GL	07.11.2014

For closing pre-threaded holes



Application range

Control cabinet manufacturing
Distribution box
Junction boxes

Product Make-up

PG connection thread

Note

SKINDICHT® BLK-GL offers high stability due to glass fibre reinforcement

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data

On request:	with O-ring fitted
Classification:	ETIM 5.0 Class-ID: EC000032 ETIM 5.0 Class-Description: plug for cable screw gland
Colour delivered:	Light grey (RAL 7035)
Material:	BLK: polystyrene BLK-GL: glass fibre-reinforced polyamide
Protection rating:	IP 54 IP 68 - 5 bar (with O-Ring)
Temperature range:	BLK: -20 °C to +70 °C BLK-GL: -40 °C to +100 °C





Product Management	Document: LAPP_PRO1103EN.pdf	1 / 3
--------------------	------------------------------	-------

SKINDICHT® BLK / BLK-GL

07.11.2014

Part number	Article designation / size	Thread length/ D (mm)	Pieces / PU
SKINDICHT® BLK			
52005949	BLK 7	6.0	100
52005950	BLK 9	6.0	100
52005960	BLK 11	6.0	100
52005970	BLK 13,5	6.0	100
52005980	BLK 16	6.0	100
52005990	BLK 21	8.0	50
52006000	BLK 29	8.0	50
52006010	BLK 36	10.0	25
52006020	BLK 42	10.0	25
52006030	BLK 48	12.0	25
SKINDICHT® BLK-GL			
52024848	BLK - GL 7	6.0	100
52024849	BLK - GL 9	6.0	100
52024850	BLK - GL 11	6.0	100
52024851	BLK - GL 13,5	6.0	100
52024852	BLK - GL 16	6.0	100
52024853	BLK - GL 21	8.0	50
52024854	BLK - GL 29	8.0	50
52024855	BLK - GL 36	10.0	25
52024856	BLK - GL 42	10.0	25
52024857	BLK - GL 48	12.0	25

U.I. Lapp GmbH	PRODUCT INFORMATION	 LAPP GROUP
	SKINDICHT® BLK / BLK-GL	07.11.2014



Product Management	Document: LAPP_PRO1103EN.pdf	3 / 3
--------------------	------------------------------	-------