



Specifications		
Nominal Voltage [V]	3,6	
Minimum capacity [mAh]	1600	
Typical capacity [mAh]	1660	
Size [mm]	According to the drawing	
Weight [g]	80 ± 25	
Typical charge [mA]	160mA for 16 hrs at 20°C	
Standard continuous discharge current [mA]	320 (temp. 20°C)	
Discharge cut-off voltage [V]	3	
Charge temperature	Typical	0°C do 50°C
Discharge temperature	Continous	-10°C do 65°C
Storage temperature	Recommended	-20°C do 30°C

Material/ Materiał:	Scale/ Skala: 1:2	Format/ Format arkusza: A4	Weight/ Masa: _	Sheet/ Arkusz: /	Version/ Wersja: 1	
Finishing/ Wykończenie :	Date/ Data:				Revision/ Rewizja: A	
Designed by/ Konstruował:	dd.mm.yyyy					ERP system number:
Checked by/ Sprawdził:	dd.mm.yyyy					
Approved by/ Zatwierdził:	dd.mm.yyyy					
Update/ Aktualizował:	Update/ Data aktualizacji:					
J. Wierzba	2016-09-19	2016-08-30	CL-AA_HT3.6V_L 3S1P HAA1600HT	1482.00.00.1A		