

Product information CM 02 E 20-27 P

Industrial Connectors:Circular connector CM-series:Surface mounted connector:CM 02 E 20-27 P

http://e-catalog.hirschmann.com/link/57078-24228-24363-24365-36156/en/conf/uistate

Name CM 02 E 20-27 P



	Surface mounted connector, with flange, with solder bucket
Delivery informations	
Availability	available
Product description	
Description	Surface mounted connector, with flange, with solder bucket
Туре	CM 02 E 20-27 P
Order No.	933 062-100
Number of contacts	14 + PE
Cable diameter	12 mm bis 14 mm
Conductor size	max. 1.5 mm ²
Standard	MIL-C 5015 bzw. VG 95 342
Housing Color	black
Technical data	
Pin dimensions	1.6 mm
Rated voltage	AC/DC 50 V
Rated current	10 A
Contact resistance	<= 5 m0hm
Type of termination	solder
Shell size	20
Mounting	screws
Material	
Contact surface material	Ag
Contact bearer material	PA 66-GF 25
Housing material	PA 66-GF 25
Environmental conditions	
Protection class (IEC 60529)	IP 67
Pollution severity	3
Temperature range	-40 °C to +90 °C
Anbauflächentemperatur	up to 100 °C
Inflammability class	
Flammability, UL standard	94 V-1
Packing unit	
Packaging unit	100 pieces
Scope of delivery and accessories	
Scope of delivery	1 surface mounted connector
Accessories to order separately	can be plugged into CM 06 EA 20-27S; flat gasket CM 02 D 20, order no. 733 818-002; cap CM 02 SD 20, order no. 831 766-100;






Industrial Connectors:Circular connector CM-series:Surface mounted connector:CM 02 E 20-27 P

http://e-catalog.hirschmann.com/link/57078-24228-24363-24365-36156/en/conf/uistate

Picture

Drawing



Belden Deutschland GmbH

lm Gewerbepark 2 58579 Schalksmühle

Germany

Phone: +49 7127/14-1806 E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.

