

DIGITUS Professional VGA Splitter 500MHz, 4-Port

DS-42110
EAN 4016032323815



Video Splitter 1 PC, 4 Monitors 500 MHz,HDSUB 15/M - 4 X HDSUB 15/F Max. Res. 2048x1536p

With a video splitter you can use one video source to display identical images on 2, 4, 8, or 16 monitors - or on even more screens by means of cascading. Thus, a video splitter can be used in various application fields, e.g. test bench facilities, data centers, help desks, video broadcasting, presentations and educational facilities.

Provides simultaneous display on four different monitors - Perfect for classrooms, tradeshow, or in-store displays!

- Enables to split a video-signal from a PC onto 4 monitors, or other video output devices

- Video bandwidth: 500MHz
- Max. resolution: 2048x1536p @60Hz
- Max. transmission distance: 75m
- Cascadable (max. 64)
- Metal housing for better EMI shielding
- DDC, DDC2, DDC2B support
- Video IN/OUT: HD DSUB, 15-pin, jacks

Lieferumfang

- VGA splitter 500MHz, 4-port
- Power supply
- Manual

Logistische Daten						
	Anzahl (Stück)	Gewicht (kg)	Tiefe (cm)	Breite (cm)	Höhe (cm)	cm ³
Karton-VPE	10	7,50	32,00	27,00	32,50	28.080,00
Innen-VPE	1	0,75	6,00	25,00	15,00	2.250,00
Einzel-VPE	1	0,75	6,00	25,00	15,00	2.250,00
Netto einzeln ohne VP	1	0,00	0,00	0,00	0,00	0,00



Weitere Anwendungsbilder:

