

FEATURES:

Meets energy star level VI

MTBF – 50 000 h

DC Cable - L=1200mm

OCP / OVP / SC


SPECIFICATION:

output	Model	Voltage DC [V]	Current min [A]	Current max. [A]	Tolerance [%]	Efficiency [%]	Power max. [W]	Ripple & noise [mV]	DC plug	
	ESPE -1224-W2E	24	0	0.5	+/- 5	>82	12	300	2.1x5.5x11	
input	voltage					100 - 240V				
	voltage range					90 - 264V				
	frequency min. / max					47 - 63 Hz				
	frequency					60HZ / 50Hz				
	variation Frequency					47-63Hz				
	current					0.35 Amax @ 115VAC				
	inrush current					30 Amax @ 230VAC				
leakage current					0,25mA @ 264WAC					
protection	OCP					Overload				
	OVP					Over voltage				
	SC					Short circuit				
	insulation					Class II				
	min. load requirement					No				
others	MTBF					50000h				
	efficiency					> 82 %				
	dimensions / weight					69 x 27 x 38 mm / 80g				
environmental	operating temp.					0 ~40 deg C				
	storage temp.					-10 ~85 deg C				
	relative humidity					5 ~90% RH				
	storage relative humidity					5% ~90% RH				
safety	CE					EN 60950-1				
	TUV - GS					EN 60950-1				
EMC	EMI					EN 55022 CLASS B				
	EMS					EN 61000-3-2, EN 61000-3-3, EN 61000-4-2, EN 6100-4-3, EN 6100-4-4, EN 61000-4-5, EN 61000-4-6 EN 61000-4-8, EN 61000-4-11				