

FEATURES:

Slim wall socket housing

MTBF – 50 000 h

Meets energy star level V



SPECIFICATION:

output	Model	Voltage DC [V]	Current min [A]	Current max. [A]	Tolerance [%]	Efficiency [%]	Power max. [W]	Ripple & noise [mV]	DC plug	
	ESPE 1005 microUSB	5	0.01	2	+/- 5	>72	10	100	microUSB	
input	voltage					100 - 240V				
	voltage range					90 - 264V				
	frequency min. / max					47 - 63 Hz				
	frequency					60HZ / 50Hz				
	current					0,3 Amax				
	inrush current					30Amax@240VAC				
protection	OCP					Overload				
	OVP					Over voltage				
	SC					Short circuit				
	insulation					Class II				
	min. load requirement					0,01				
others	MTBF					50000h				
	efficiency					> 72 %				
	dimensions / weight					70 x 27 x 38 mm / 90g (100pcs/cartoon)				
environmental	operating temp.					0 ~40 deg C				
	storage temp.					-10 ~80 deg C				
	relative humidity					25 ~75% RH				
	storage relative humidity					25% ~75% RH				
safety	CE					EN60950-1				
	TUV - GS					EN60950-1				
EMC	EMI					EN 55022:1998, +A1:2000 +A2:2003, CLASS B CISPR 22:2003, CLASS B AS/NZS CISPR22: 2004, CLASS B				
	EMS					EN 61000-3-2, EN 61000-3-3, EN 61000-4-2, EN 6100-4-3, EN 6100-4-4, EN61000-4-5, EN61000-4-6 EN 61000-4-8, EN 61000-4-11				